


STRETCHER COMPATIBLE MRL TRACTION ELEVATORS AND HYDRAULIC ELEVATORS

GMV has both machine room less and hydraulic elevators that meet stretcher requirements.


The International Building Code specifies that any building "four or more stories above, or four or more stories below grade plane" shall have at least one elevator car that is able to accommodate a standard 24" x 84"* (610 mm x 2134 mm) ambulance stretcher in the open, horizontal position.

Some GMV EDGE series hydraulic passenger elevator cabs and GMV ICON series MRL traction elevator cabs meet the International Building Code stretcher requirements.


**Different codes may be applicable in Florida and other jurisdictions.*




Front Only (Inline) - Standard



Front Only (Inline) - Deep



Front and Rear (Thru-Cab) - Standard



Front and Rear (Thru-Cab) - Deep

Capacity lbs	Type	Opening Side	Door Width	IBC Stretcher (84")	OBC Stretcher (79")	FL Stretcher (76")
2100	STANDARD	Side	42"	N	N	N
2500		Side	42"	N	Y	Y
3000		Side	42"	Y(Angle)	Y	Y
3500		Side	42"	Y(Angle)	Y	Y
2300	DEEP	Side	42"	N	N	Y(Angle)
2890		Side	42"	Y	Y	Y
3500		Side	42"	Y	Y	Y
4000		Side	42"	Y	Y	Y
4000		Side	48"	Y	Y	Y